

# MT5-Pro

# 575-595W

N-type TOPCon  
Bifacial Dual Glass Solar Module


## Qualidade Garantida

**25-Year** Warranty for Materials and Processing

**30-Year** Warranty for Extra Linear Power Output

23.02%

Max. Module Efficiency



MS-72H

## 10-30% Additional Power Generation

30 years lifespan brings 10-30% additional power generation comparing with conventional P-type module.

## ZERO LID (Light Induced Degradation)

N-type solar cell has no LID naturally which can increase power generation.

## Higher Reliability


Adopted Mate Solar latest S-TOPCo 2.0 technology, No polysilicon wrap around, Full electrical isolation, Zero leakage current; Much Safer for roof.

## Better Weak Illumination Response

Higher power output even under low-light environments like on cloudy or foggy days.

## Better Temperature Coefficient

Higher power generation under working conditions, thanks to passivating contact cell technology.



\* Please refer to Mate Solar standard warranty for details

## Quality Management System And Product Certification

IEC61215/61730, IEC62804(PID), IEC61701(Salt).

IEC62716 (Ammonia), IEC60068-2-68(Sand).

ISO 9001:2015/quality management system.

ISO 14001:2015/environmental management system.


ISO 45001:2018/occupation health safety management system

ISO 50001:2011/energy management system.


IEC TS 62941-2016/PV industry quality management system .



**Drawings**



**Product Image**



**Mechanical Parameters**

Solar Cells	N-type Mono
No. of Cells	144 (6×24)
Dimensions	2278 x 1134 x 30mm
Weight	31.5kg
Glass	Front: 2.0mm coated semi-tempered glass; Back: 2.0mm semi-tempered glass
Frame	Anodized aluminium alloy
Junction Box	Ip68 rated (3 by pass diodes)
Output Cables	4mm <sup>2</sup> , 300mm (+) / 300mm (-), Length can be customized
Connectors	Mc4 compatible
Mechanical load test	5400Pa
Packaging	36pcs/box, 180pcs/20'GP, 720pcs/40'HQ

**Operating Characteristics**

Operating Module Temperature	-40°C to +85°C
Maximum System Voltage	1500 DC (IEC)
Maximum Series Fuse Rating	30A
Power Tolerance	0/+5W



**Temperature Characteristics**

Nominal Operating Temperature (NMOT)	45±2°C
Temperature Coefficient of Pmax	-0.29%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	+0.045%/°C

**Electrical Characteristics (STC\*)**

Module Type: MS-72H	575	580	585	590	595
Maximum power (Pmax/W)	575	580	585	590	595
Open Circuit Voltage (Voc/V)	52.15	52.31	52.47	52.63	52.79
Short Circuit Current (Isc/A)	13.95	14.01	14.07	14.13	14.19
Voltage at Maximum power (Vmpp/V)	43.17	43.35	43.53	43.71	43.88
Current Maximum Power (Impp/A)	13.32	13.38	13.44	13.50	13.56
MODULE EFFICIENCY (%)	22.25	22.44	22.64	22.83	23.02

**I-V Curve**



**Bifacial Output-Rearside Power Gain**

%	Maximum Power (Pmax/W)		Module Efficiency STC (%)	
	575	580	585	590
5%	604	609	614	620
	23.36	23.56	23.77	23.97
15%	661	667	673	679
	25.59	25.81	26.03	26.25
25%	719	725	731	738
	27.81	28.05	28.29	28.54

1. Standard Test Conditions [STC]: irradiance 1000W/m<sup>2</sup>; AM 1.5; ambient temperature 25°C according to EN 60904-3;  
 2. Tolerance of Pm: 0-+5W, Measuring uncertainty of power: ±3%. Performance deviation of Voc [V], Isc [A], Vm [V] and Im [A]: ±3%.